



# Safety Data Sheet

## 1. Identification of the substance / preparation and the Company

### 1.1 Identification of the substance or preparation

Product name DILUENTE MEDIO: PLA

### 1.2 Use of the substance / preparation

Intended use Pad printing thinner

### 1.3 Company identification

Name COMEC ITALIA SRL  
Full address PIAZZALE DEL LAVORO 149  
District and Country 21044 CAVARIA VA  
ITALIA  
Tel. 0331 219516  
Fax 0331 216161

e-mail address of the competent person responsible for the Safety Data Sheet info@comec-italia.it

Product distribution by EDGARDO BAGGINI

### 1.4 Emergency telephone

## 2. Hazards Identification

### 2.1 Substance/Preparation Classification

This product is dangerous under 67/548/EEC and 1999/45/EC directives and subsequent amendments. Therefore, this product requires a safety data sheet according to the Regulation (EC) 1907/2006 and subsequent amendments. Further information on health and/or environmental hazards can be found in sections 11 and 12 of this sheet.

Danger Symbols: Xn-N  
R phrases: 10-20-37-51/53-65-66

### 2.2 Danger Identification

Because of its chemical-physical features, this product is graded as flammable (flash-point 21 °C or higher and 55 °C or lower ).

HARMFUL BY INHALATION.

IRRITATING TO RESPIRATORY SYSTEM.

TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT.

HARMFUL: MAY CAUSE LUNG DAMAGE IF SWALLOWED.

REPEATED EXPOSURE MAY CAUSE SKIN DRYNESS OR CRACKING.

### 3. Composition / Information on ingredients

Contains:

Name	Concentration % (C)	Classification
1-METHOXY-2-PROPANOL ACETATE CAS No 108-65-6 CE No 203-603-9 Index No 607-195-00-7	15 <= C < 16,5	R10 Xi R36
CYCLOHEXANONE CAS No 108-94-1 CE No 203-631-1 Index No 606-010-00-7	32,5 <= C < 35	R10 Xn R20
N-BUTYL ACETATE CAS No 123-86-4 CE No 204-658-1 Index No 607-025-00-1	15 <= C < 16,5	R10 R66 R67
SOLVENT NAPHTA (PETROLEUM), LIGHT AROM CAS No 64742-95-6 CE No 265-199-0 Index No 649-356-00-4	35 <= C < 37,5	R10 R66 R67 Xn R65 Xi R37 N R51/53 Note H P 4

The complete text of -R- phrases is specified in section 16.

### 4. First aid measures

**EYES:** Irrigate copiously with clean, fresh water for at least 15 minutes. Seek medical advice.

**SKIN:** Wash immediately with plenty of water. Remove contaminated clothing. If irritation persists, seek medical attention. Wash contaminated clothing before using them again.

**INHALATION:** Remove to open air. If breathing is irregular, seek medical advice.

**INGESTION:** Obtain immediate medical attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person.

### 5. Fire-fighting measures

#### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Excess pressure may form in containers exposed to fire at a risk of explosion. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water and the remains of the fire according to applicable regulations.

#### SUITABLE EXTINGUISHING MEDIA

The extinction equipment should contain carbon dioxide, foam or chemical powders. For product leaks and spills that have not caught fire, nebulised water can be used to disperse flammable fumes and protect the individuals taking part in stemming the leak.

#### EXTINGUISHING MEDIA WHICH SHALL NOT BE USED FOR SAFETY REASONS

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

**HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

Do not breathe combustion products (carbon oxide, toxic pyrolysis products, etc).

**SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS**

Hardhat with visor, fireproof clothing (fireproof jacket and trousers with ties around arms, legs and waist) work gloves (fireproof, cut proof and dielectric), self-respirator (self-protector).

**6. Accidental release measures**

**PERSONAL PRECAUTIONS**

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. If there are no contraindications, spray solid products with water to prevent the formation of dust. Use breathing equipment if fumes or powders are released into the air. Block the leakage if there is no hazard. Do not handle damaged containers or the leaked product before donning appropriate protective gear. For information on risks for the environmental and health, respiratory tract protection, ventilation and personal protection equipment, see the other sections of this sheet.

**ENVIRONMENTAL PRECAUTIONS**

The product must not penetrate the sewers, surface water, ground water and neighbouring areas.

**METHODS FOR CLEANING UP**

Use inert absorbent material (sand, vermiculite, diatomaceous earth, Kieselguhr, etc.) to soak up leaked product. Collect the majority of the remaining material and deposit it in containers for disposal. If there are no contraindications, use jets of water to eliminate product residues. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

**7. Handling and storage**

Store in a well ventilated place, keeping the containers closed when not used. Do not smoke while handling. Keep far away from sources of heat, bright flames and sparks and other sources of ignition.

**8. Exposure control / personal protection.**

**8.1 Exposure limit values**

Name	Type	Country	TWA/8h		STEL/15min		
			mg/m3	ppm	mg/m3	ppm	
1-METHOXY-2-PROPANOL ACETATE	OEL	EU	275	50	550	100	Skin
	OEL	IRL		50		100	Skin
	WEL	UK		50		100	Skin
CYCLOHEXANONE	TLV-ACGIH		80		200		Skin
	OEL	EU	40,8	10	81,6	20	Skin
	OEL	IRL		10		20	Skin
	WEL	UK		10		20	Skin
N-BUTYL ACETATE	TLV-ACGIH		713		950		
	OEL	IRL		150		200	
	WEL	UK		150		200	

## 8.2 Exposure controls

As the use of adequate technical equipment must always take priority over personal protection equipment, make sure that the workplace is well aired through effective local aspiration or bad air vent. If such operations do not make it possible to keep the concentration of the product below the permitted workplace exposure thresholds a suitable respiratory tract protection must be used. See product label for hazard details during use. Ask your chemical substance suppliers for advice when choosing personal protection equipment. Personal protection equipment must comply with the rules in force indicated below.

### HAND PROTECTION

Protect hands with category II (ref. Directive 89/686/EEC and standard EN 374) work gloves, such as those in PVC, neoprene, nitril or equivalent. The following should be considered when choosing work glove material: degradation, breakage times and permeation. Work glove resistance to preparations should be checked before use, as it can be unpredictable. Gloves' limit depends on the duration of exposure.

### EYE PROTECTION

Wear protective airtight goggles (ref. standard EN 166).

### SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (ref. Directive 89/686/CEE and standard EN 344). Wash body with soap and water after removing overalls.

### RESPIRATORY PROTECTION

If the threshold value for one or more of the substances present in the preparation for daily exposure in the workplace or to a fraction established by the company's prevention and protection service is exceeded, wear a mask with an B or universal filter, the class (1, 2 or 3) of which must be chosen according to the limit concentration of use (ref. standard EN 141).

The use of breathing protection equipment, such as masks with organic vapour and dust/mist cartridges, is necessary in the absence of technical measures limiting worker exposure. The protection provided by masks is in any case limited.

If the substance in question is odourless or its olfactory threshold is higher than the relative exposure limit and in the event of an emergency, or when exposure levels are unknown or the concentration of oxygen in the workplace is less than 17% volume, wear self-contained, open-circuit compressed air breathing apparatus (ref. standard EN 137) or fresh air hose breathing apparatus for use with full face mask, half mask or mouthpiece (ref. standard EN 138).

An emergency eye washing and shower system must be provided.

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

## 9. Physical and chemical properties

Colour	transparent
Odour	typical of solvent
Physical state	liquid
Solubility	partial soluble in water
Viscosity	Not available
Vapour density	> 1 (aria =1)
Evaporation speed	Not available
Comburent properties	Not available
Partition coefficient: n-octanol/water	Not available
pH	Not available
Boiling point	>125°C
Flash point	>21°C
Explosive properties	Not available
Vapour pressure	Not available
Specific gravity	Not available

## 10. Stability and reactivity

The product is stable in normal conditions of use and storage. When heated or in the event of a fire, carbon oxides may be released and vapours which are dangerous to health. The vapours may also form explosive mixtures with the air.

1-methyl-2-methoxyethyl acetate: it is stable but in presence of air, it can gradually form peroxides which explode due to the rise in temperature. It can react violently with oxidizing agents and strong acids and alkaline metals. Avoid copper, aluminium and their alloys when storing. Store under inert atmosphere, repaired from humidity because it easily hydrolyses.

Cyclohexanone reacts violently with strong oxidizing agents and attacks different types of plastic materials (ref. H.C.S.).

Nbutyl acetate easily decomposes with water especially when heated.

## 11. Toxicological information

Acute effects: inhalation of this product is harmful. This product may irritate mucosas, the upper respiratory tract, eyes and skin. Exposure symptoms may include: stinging and irritated eyes, mouth, nose, throat; cough, respiratory disorders, dizziness, headache, nausea and sickness.

In the most serious cases, inhalation of this product may cause larynx and bronchial tube edema and irritation, chemical pneumonia and pulmonary edema. Ingestion of even small amounts of product may cause health problems (stomach pain, nausea, sickness, diarrhoea).

The introduction of even small quantities of this liquid into the respiratory system in case of ingestion or vomit may cause bronchopneumonia and pulmonary edema.

This product may have a degreasing action on the skin, producing dryness and chapped skin after repeated exposure.

N-butyl acetate: the vapours are particularly irritating to the eyes and respiratory tract and at high concentrations they are also narcotic. Frequent contact with the skin may cause dermatitis (INR nr. 31, 1987).

2-METHOXY-1-METHYLETHYL ACETATE: oral LD50 (mg/kg) > 5000 (RAT) ; dermal LD50 (mg/kg) > 5000 (RAT).

## 12. Ecological information

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it may even have negative effects on aquatic environment.

## 13. Disposal consideration

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

### CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

## 14. Transport information

These goods must be transported by vehicles authorized to the carriage of dangerous goods according to the provisions set out in the current edition of the Code of International Carriage of Dangerous Goods by Road (ADR) and in all the applicable national regulations. These goods must be packed in their original packagings or in packagings made of materials resistant to their content and not reacting dangerously with it. People loading and unloading dangerous goods must be trained on all the risks deriving from these substances and on all actions that must be taken in case of emergency situations.

### Road and rail transport:

ADR/RID Class:	3
UN:	1993
Packing Group:	III
Label:	3
Nr. Kemler:	30
Limited Quantity	LQ07
Tunnel restriction code	(D/E)
Proper Shipping Name:	Flammable liquid, n.o.s. (Cyclohexanone; ACETATE 1-METHYL-2-methoxyethyl)
Special Provision:	640E



### Carriage by sea (shipping):

IMO Class:	3
UN:	1993
Packing Group:	III
Label:	3
EMS:	F-E, S-E
Marine Pollutant	YES
Proper Shipping Name:	FLAMMABLE LIQUID, N.O.S. (SOLVENT NAPHTA (PETROLEUM), LIGHT AROM; CYCLOHEXANONE)





### Transport by air:

IATA:	3
UN:	1993
Packing Group:	III
Label:	3
Cargo:	
Packaging instructions:	310
Maximum quantity:	220 L
Pass.:	
Packaging instructions:	309
Maximum quantity:	60 L
Special Instructions:	A3
Proper Shipping Name:	FLAMMABLE LIQUID, N.O.S. (SOLVENT NAPHTA (PETROLEUM), LIGHT AROM; CYCLOHEXANONE)



## 15. Regulatory information



**HARMFUL****DANGEROUS FOR THE  
ENVIRONMENT**

R10	FLAMMABLE.
R20	HARMFUL BY INHALATION.
R37	IRRITATING TO RESPIRATORY SYSTEM.
R51/53	TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT.
R65	HARMFUL: MAY CAUSE LUNG DAMAGE IF SWALLOWED.
R66	REPEATED EXPOSURE MAY CAUSE SKIN DRYNESS OR CRACKING.
S 7/ 9	KEEP CONTAINER TIGHTLY CLOSED AND IN A WELL-VENTILATED PLACE.
S16	KEEP AWAY FROM SOURCES OF IGNITION - NO SMOKING.
S62	IF SWALLOWED, DO NOT INDUCE VOMITING: SEEK MEDICAL ADVICE IMMEDIATELY AND SHOW THIS CONTAINER OR LABEL.

**Contains:**

CYCLOHEXANONE  
SOLVENT NAPHTA (PETROLEUM), LIGHT AROM

Danger labelling under directives 67/548/EEC and 1999/45/EC and following amendments and adjustments.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

**16. Other information**

Text of -R- phrases quoted in section 3 of the sheet.

R10	FLAMMABLE.
R20	HARMFUL BY INHALATION.
R36	IRRITATING TO EYES.
R37	IRRITATING TO RESPIRATORY SYSTEM.
R51/53	TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT.
R65	HARMFUL: MAY CAUSE LUNG DAMAGE IF SWALLOWED.
R66	REPEATED EXPOSURE MAY CAUSE SKIN DRYNESS OR CRACKING.
R67	VAPOURS MAY CAUSE DROWSINESS AND DIZZINESS.

**GENERAL BIBLIOGRAPHY**

1. Directive 1999/45/EC and following amendments;
2. Directive 67/548/EEC and following amendments and adjustments (technical adjustment XXIX);
3. Regulation (EC) 1272/2008 (CLP) of the European Parliament;
4. Regulation (EC) 1907/2006 (REACH) of the European Parliament;
5. The Merck Index. - 10th Edition;
6. Handling Chemical Safety;
7. Niosh - Registry of Toxic Effects of Chemical Substances;
8. INRS - Fiche Toxicologique (toxicological sheet);
9. Patty - Industrial Hygiene and Toxicology;
10. N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition;



## COMEC ITALIA SRL DILUENTE MEDIO PLA

Revision nr. 3  
Dated 02/11/2010  
Printed on 02/11/2010  
Page n.8 / 8

### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product .

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

PRODUCT FOR PROFESSIONAL USE ONLY.

Changes to previous review

The following sections were modified:

03 / 06